

SOLANCHE 3565 PFS70

Product information

Application Outside

System Hanging | Sliding

Color Top side black, Bottom side white

Feature Shading, Solar protection

Flame retardant No

Material 34% Polyethylene, 66% Polyethylene yarn

Pattern 3 black|white film + 1 empty

Weight 138 grams | m²

Roll width Standard 3,25M, 4,30M, 5,30M. Other customized roll widths are available:

Roll length Standard 100M or 200M. Other customized roll lengths are available

Heat treatment Yes

Shrinkage $\leq 2\%$ at 70° C|2H

Warranty Please, contact us for warranty information.

Product information		Value	Unit	Test Methods
				_
Shading level in direct light PAR**		70	%	Protocol NEN 2675:2018
		70	%	Stratus method
Energy saving		0	%	Stratus method
Tensile strength	Warp	289	MPa	
	Weft	421	MPa	
Screen weight		138	g/m^2	
Width of strips		4,6	mm	

Width 50 mm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, **Stratus Climate Screens** does not accept any liability in respect of its accuracy. Further information concerning the product and its installation may be obtained from **Stratus Climate Screens B.V.**

Products marked FR are flame retardant.

^{**} PAR = 400 - 700 nm, accuracy +/- 1%

^{***} UV-light = 300 - 400 nm