

SOLANCHE 3550 PFS60

Product information

Application	Outside
System	Hanging Sliding
Color	Top side black, Bottom side white
Feature	Shading, Solar protection
Flame retardant	No
Material	30% Polyethylene, 70% Polyethylene yarn
Pattern	2 black white film + 1 empty
Weight	133 grams m ²
Roll width	Standard 3,25M, 4,30M, 5,30M. Other customized roll widths are available:
Roll length	Standard 100M or 200M. Other customized roll lengths are available
Heat treatment	Yes
Shrinkage	≤2% at 70°C 2H
Warranty	Please, contact us for warranty information.

Product information		Value	Unit	Test Methods
Shading level in direct light PAR**		60	%	Protocol NEN 2675:2018
		60	%	Stratus method
Energy saving		0	%	Stratus method
Tensile strength	Warp	289	MPa	
	Weft	421	MPa	
Screen weight		133	g/m ²	
Width of strips		4,6	mm	

Width 50 mm

** PAR = 400 - 700 nm, accuracy +/- 1%

*** UV-light = 300 - 400 nm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, **Stratus Climate Screens** does not accept any liability in respect of its accuracy. Further information concerning the product and its installation may be obtained from **Stratus Climate Screens B.V.**

Products marked FR are flame retardant.