

LUMINUS 2215 FR SE2540

Product information

Application	Inside
System	Hanging Sliding
Color	Transparent
Feature	Energy saving, Shading
Flame retardant	Yes, NTA 8825:2010
Material	48% FR Polyester, 52% FR Polyester yarn
Pattern	Full transparent
Weight	85 grams m ²
Roll width	Standard 3,25M, 4,30M, 5,30M. Other customized roll widths are available
Roll length	Standard 100M or 200M. Other customized roll lengths are available
Heat treatment	Yes
Shrinkage	≤2% at 70°C 2H
Weave	Closed
Warranty	Please, contact us for warranty information.

Product information		Value	Unit	Test Methods
Shading level in direct light PAR**		30	%	Protocol NEN 2675:2018
		25	%	Stratus method
Energy saving		40	%	Stratus method
Tensile strength	Warp	330	MPa	
	Weft	405	MPa	
Screen weight		85	g/m ²	
Width of strips		3,8	mm	

Width 50 mm

** PAR = 400 - 700 nm, accuracy +/- 1%

*** UV-light = 300 - 400 nm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, **Stratus Climate Screens** does not accept any liability in respect of its accuracy. Further information concerning the product and its installation may be obtained from **Stratus Climate Screens B.V.**

Products marked FR are flame retardant.