

OPTIMA 1200 FR W|W or B|W

Product information

Application	Inside, closed structure
System	Rolling
Function	Darkness control Total black out
Color	White White or Black White
Feature	Light deprivation Blackout Energy saving
Flame retardant	Yes, conform NTA 8825:2010, Class 2
Material	Polyolefin 100%
Pattern	Laminated
Weight	200 grams m ² Other available weights: 220, 230 and 250 grams m ²
Roll width	Standard 2,90M. Customized roll widths are available: 2,50M-5,80M
Roll lengths	Standard 100M, 200M, 500M. Customized roll lengths are available upto 1,500M
Warranty	Please, contact us for warranty information.

Product information	Value	Unit	Test Methods
Shading level in diffused light PAR**	99.9	%	Stratus method
Shading level in direct light PAR**	99.9	%	Stratus method
UV light transmission ***	0	%	Stratus method
Energy saving	70	%	Stratus method
Screen Weight	200	g/m ²	
[upon request different screen weights available]			
Thickness	0.35	mm	
Elongation (length / width) *	15/17 %		According to ISO 13934- 1

Width 50 mm

** PAR = 400 - 700 nm, accuracy +/- 1%

*** UV-light = 300 - 400 nm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, **Stratus Climate Screens** does not accept any liability in respect of its accuracy. Further information concerning the product and its installation may be obtained from **Stratus Climate Screens B.V.**

Products marked FR are flame retardant.