

SOLANCHE 3600 SE6562

Product information

Application	Inside, close structure
System	Hanging Sliding
Color	White
Feature	Energy saving, Solar Protection
Flame retardant	No
Material	Polyester, Polyethylene, Polyester yarn
Pattern	3 white diffuse + 1 polyester
Weight	75 grams m ²
Roll width	Standard 3,25M, 4,30M, 5,30M. Other customized roll widths are available:
Roll length	Standard 100M or 200M. Other customized roll lengths are available
Heat treatment	Yes
Shrinkage	≤2% at 70°C 2H
Warranty	Please, contact us for warranty information.

Product information		Value	Unit	Test Methods
Shading level in direct light PAR**		65	%	Protocol NEN 2675:2018
		65	%	Stratus method
Energy saving		62	%	Stratus method
Tensile strength	Warp		MPa	
	Weft		MPa	
Screen weight		75	g/m ²	
Width of strips		3,8	mm	

Width 50 mm

** PAR = 400 - 700 nm, accuracy +/- 1%

*** UV-light = 300 - 400 nm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, **Stratus Climate Screens** does not accept any liability in respect of its accuracy. Further information concerning the product and its installation may be obtained from **Stratus Climate Screens B.V.**

Products marked FR are flame retardant.