

## SPARO 1250 SE3552

## **Product information**

Application Inside, close structure System Hanging | Sliding

Color White

Feature Energy saving, Light distribution

Flame retardant No

Material Polyester, Polyethylene, Polyester yarn
Pattern 1 White diffuse | 1 Transparent diffuse

Weight 85 grams | m<sup>2</sup>

Roll width Standard 3,25M, 4,30M, 5,30M. Other customized roll widths are available:

Roll length Standard 100M or 200M. Other customized roll lengths are available

Heat treatment Yes

Shrinkage  $\leq 2\%$  at  $70^{\circ}$ C|2H

Warranty Please, contact us for warranty information.

| Product information                 |                  | Value<br>35 | Unit %  | Test Methods  Protocol NEN 2675:2018 |
|-------------------------------------|------------------|-------------|---------|--------------------------------------|
| Shading level in direct light PAR** |                  |             |         |                                      |
|                                     | oct iight 11 iit | 35          | %       | Stratus method                       |
| Energy saving                       |                  | 52          | 0/0     | Stratus method                       |
| Tensile strength                    | Warp             |             | MPa     |                                      |
|                                     | Weft             |             | MPA     |                                      |
| Screen weight                       |                  | 85          | $g/m^2$ |                                      |
| Width of strips                     |                  | 3,8         | mm      |                                      |

Width 50 mm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, **Stratus Climate Screens** does not accept any liability in respect of its accuracy. Further information concerning the product and its installation may be obtained from **Stratus Climate Screens B.V.** 

Products marked FR are flame retardant.

<sup>\*\*</sup> PAR = 400 - 700 nm, accuracy +/- 1%

<sup>\*\*\*</sup> UV-light = 300 - 400 nm