

OPTIMA 1375 AB

Product information

Application	Inside, closed system
System	Rolling
Function	Darkness control Total black out
Color	Top aluminium, Bottom black
Feature	Blackout Energy saving
Flame retardant	No
Material	Aluminium, Polyester, Polyester yarn
Pattern	99% full
Weight	95 grams m ²
Roll width	Standard 3,25M, 4,30M, 5,30M. Other customized roll widths are available
Roll lengths	Standard 100M or 200M. Other customized roll lengths are available
Heat treatment	Yes
Shrinkage	≤2% at 70°C 2H
Warranty	Please, contact us for warranty information.

Product information	Value	Unit	Test Methods
Shading level in diffused light PAR**	99.9	%	Stratus method
Shading level in direct light PAR**	99.9	%	Stratus method
UV light transmission ***	0	%	Stratus method
Energy saving	75	%	Stratus method
Screen Weight	95	g/m ²	
Width of strips	3,9	mm	

Width 50 mm

** PAR = 400 - 700 nm, accuracy +/- 1%

*** UV-light = 300 - 400 nm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, **Stratus Climate Screens** does not accept any liability in respect of its accuracy. Further information concerning the product and its installation may be obtained from **Stratus Climate Screens B.V.**

Products marked FR are flame retardant.